## **DECLARATION OF PERFORMANCE**



No: DoP\_ChrB\_ENG\_2015-001

1. Product type unique identification code:

**Tilestove Christineberg** 

2. Intended use:

Fireplace for heating and comfort for connection to Fluegaspipe/Chimney.

3. Manufacturer:

Keddy AB, Box 542, 44115 Alingsås, telephone +46 322 78180

4. Authorised representatives:

5. The system or systems of assessment and continuous monitoring of product performance:

System 3.

6a. Harmonized standard:

SS-EN 13240: 2001, SS-EN 13240/A2: 2004/AC: 2006 Notified body nr: 1625 Rhein – Ruhr Feuerstätten Prufstelle. Report nr: RRF – 40 12 3036

7. Essential characteristics:

Specified performance for these products: Tilestove Christineberg

Essential feature	Performance
Fire safety	Pass
Flue gas temperature	170 °C
Fluepipe spigot	Pass (40mm)
Other fire characteristics. (eg risk of falling embers)	Pass
Discharge of combustion products	
CO - emission	0,09%
Flue gas Channel	Pass
Release of hazardous substances	NPD
Surface temperature	
Distance to combustible rear	10cm
Distance to combustible side	10cm
Fuel storage location	Pass
Temperature handle	Pass, with cool hand tool
Mechanical strength (to support fluepipe/chimney)	Pass
Thermal effect	9 kW
Efficiency	85%

Signed for and on behalf of the manufacturer by:

Development Manager, Keddy AB

Alingsås 2015-09-16

( (

Art: 193675