

## DECLARATION OF PERFORMANCE

No: DoP\_ K700\_ENG\_2015-001

1. Product type unique identification code:

**Wood Buring Stove K700**

2. Intended use:

**Fireplace for heating and comfort for connection to Fluegaspipe/Chimney.**

3. Manufacturer:

**Keddy AB, Box 542, 44115 Alingsås, telephone +46 322 78180**

4. Authorised representatives:

-

5. The system or systems of assessment and continuous monitoring of product performance:

**System 3.**

6a. Harmonized standard:

**SS-EN 13240: 2001, SS-EN 13240/A2: 2004/AC: 2006**

**Notified body nr: 1625 Rhein – Ruhr Feuerstätten Prüfstelle.**


**Report nr: RRF - 40 15 4015**

7. Essential characteristics:

**Specified performance for these products: K700**

Essential feature	Performance
Fire safety	Pass
Flue gas temperature	232 °C
Fluepipe spigot	Pass (40mm)
Other fire characteristics. (eg risk of falling embers)	Pass
<b>Discharge of combustion products</b>	
CO - emission	0,08%
Flue gas Channel	Pass
Release of hazardous substances	NPD
<b>Surface temperature</b>	
Distance to combustible rear	10 cm
Distance to combustible side	30 cm
Fuel storage location	Pass
Temperature handle	Pass with use of glove
Mechanical strength (to support fluepipe/chimney)	Pass
<b>Thermal effect</b>	
Thermal effect	5,8 kW
Efficiency	83 %

Signed for and on behalf of the manufacturer by:



Jonas Bodin  
Development Manager, Keddy AB  
Alingsås 2015-09-16

